AMENDMENT NO. 1 JUNE 2022

TO

IS 15943 : 2012 AUTOMOTIVE VEHICLES — HAND-HOLDS FOR THREE, FOUR AND MORE THAN FOUR WHEELED MOTOR VEHICLES — SPECIFICATION

[*Page* 1**,** *clause* **1**(c)] — Substitute the following for existing text:

‘c) Four wheeled vehicles registered as Transport Vehicles of categories M1 without doors, L7, M2 and M3.’

(*Page* 1*, clause* **3.2.1**) — Substitute the following for existing text:

‘**3.2.1** Following are the dimensional requirements for vehicles of category L5M, L5N, L7 and four wheelers of category M1 which are without doors, M2 upto GVW 3.5 tonnes and N1 category :

a) Length of the handhold shall be at least 100 mm to accommodate a hand of passenger;

b) Clearance between hand-hold(s) and the adjacent part of vehicle body or wall shall be of at least 25 mm;

c) Cross-sectional area measured at the middle of the length of the hand-holds other than strap shall be between 130 mm^2 and 1 500 mm^2, enabling passenger to grasp them easily and firmly; and

d) In case of straps, width measured at the middle of the length of the strap shall be 40 ± 5 mm.’

(TED 06)

Publication Unit, BIS, New Delhi, India